ReBound Diathermy System Technical Specifications

The ReBound ReGenerator

Operating Frequency: 13.56 MHz (+,-) 3kHz RF Power: 5 to 35 watts Duty Cycle: Continuous Wave

RF Connector: **BNC**

Impedance: 50 Ohms nominal

11"x9"x6"

Load Standing Wave Ratio: 1.6:1 max AC power requirements: 117 VAC, 47-63 Hz 1.5 amps 3.5 lbs. Weight:



General

Dimensions:

Input Frequency: 13.56 MHz Power Capability: 35 watts nominal

Input Connector: **BNC** Impedance: 50 Ohms Nominal

Standing Wave Ratio

Fully Loaded: <1.6:1

The Back Therapy Garment

17" x 10" x 3" Dimensions: Plus Belt Waist Sizes: 28 to 54 inches Weight: 1.5 lbs.

Cylindrical Therapy Garments 9 sizes available

Dimensions:

Nominal Length: 13 inches Circumference: 11,13,15,18,21,23,27,30,33 inches

Weight: 1 lb.

The Shoulder Garment

10" x 10" x 14" **Dimensions**

One size fits all Fits both right and left shoulder

Weight 2 lbs.



ReBound ReGenerator



Back Therapy Garment



Cylindrical Therapy Garments



Shoulder Therapy Garment